

POWER SPRAYER

SAFETY & OPERATING INSTRUCTIONS



pharmacal
RESEARCH LABORATORIES, INC.

562 Captain Neville Dr
Waterbury, CT 06705
1-800-243-5350

CAUTIONS

EACH POWER SPRAYER HAS BEEN TESTED TO MEET PRESCRIBED SPECIFICATIONS AND CERTAIN SAFETY STANDARDS. HOWEVER, A FEW PRECAUTIONARY NOTES SHOULD BE ADHERED TO AT ALL TIMES. THOROUGHLY READ ALL CAUTIONS PRIOR TO USING THE SPRAYER.

1. ALWAYS WEAR PROTECTIVE CLOTHING (PROTECTIVE GLOVES, SAFETY GLASSES) WHEN USING THE SPRAYER.
2. CHEMICALS USED MAY BE DANGEROUS AND SHOULD BE USED CAREFULLY AND ACCORDING TO WARNINGS ON THE LABEL. FOLLOW THE DIRECTIONS GIVEN WITH EACH TYPE OF CHEMICAL. DO NOT ASSUME CHEMICALS ARE THE SAME BECAUSE THEY LOOK ALIKE. ALWAYS STORE CHEMICALS IN A SAFE LOCATION AWAY FROM CHILDREN AND ANIMALS. WE CANNOT BE RESPONSIBLE FOR THE MISUSE OF CHEMICALS BEING USED THROUGH THE SPRAYER.
3. DO NOT USE FLAMABLE LIQUIDS THROUGH THE SPRAYER.
4. DO NOT DIRECT SPRAY AT PEOPLE OR ANIMALS.
5. DO NOT DIRECT SPRAY AT THE POWER SPRAYER, ELECTRICAL OUTLETS OR APPLIANCES.
6. BE SURE THAT OBJECTS TO BE SPRAYED ARE COMPATIBLE WITH THE CHEMICALS USED.
7. AVOID ELECTRICAL SHOCK HAZARD; USE ONLY GROUNDED OUTLETS. KEEP POWER CORD OUT OF PUDDLES AND AWAY FROM TRAFFIC. DO NOT USE EXTENSION CORDS.
8. DISCONNECT FROM ELECTRICAL SUPPLY BEFORE CHECKING, SERVICING, OR REMOVING COVER.
9. DO NOT ALLOW SPRAYER TO RUN UNATTENDED. TURN POWER OFF, RELEASE PRESSURE FROM GUN, AND PUT AWAY HOSE AND POWER CORD AFTER EACH USE.
10. DO NOT STORE THE POWER SPRAYER IN AN AREA WHICH MAY BE SUBJECT TO FREEZING TEMPERATURES.

GFCI POWER CORD

THE SPRAYER IS EQUIPPED WITH A GFCI (GROUND FAULT CIRCUIT INTERRUPTER) POWER CORD. THIS CORD WILL PROVIDE PROTECTION AGAINST GROUND FAULTS WHEN USED WITH A 3-WIRE ELECTRICAL OUTLET.

TO USE THE GFCI TO ITS FULLEST POTENTIAL AGAINST ELECTRICAL SHOCK, PLEASE FOLLOW THESE SIMPLE RULES:

1. DO NOT USE A 3-WIRE TO 2-WIRE ADAPTER.
2. DO NOT REMOVE THE GROUNDING PIN ON THE PLUG.
3. DO NOT USE AN EXTENSION CORD.
4. DO NOT USE IF UNIT IS DAMAGED.
5. DO NOT IMMERSE.
6. DO NOT USE THE GFCI AS AN ON/OFF SWITCH.
7. DO NOT USE THE SPRAYER IF THE "FAULT" LIGHT ON THE GFCI COMES ON AND DOES NOT GO OFF WHEN THE "RESET" BUTTON IS PRESSED.
8. TEST BEFORE EACH USE TO ENSURE SAFE OPERATION.

TEST THE GFCI POWER CORD AS FOLLOWS:

1. PLUG INTO A 115 VAC, 20 AMP RECEPTACLE.
2. PRESS THE "TEST" BUTTON ON THE GFCI. THE "FAULT" LIGHT SHOULD COME ON.
3. PRESS THE "RESET" BUTTON ON THE GFCI. THE "FAULT" LIGHT SHOULD GO OFF.

THE SPRAYER IS READY TO USE IF THE GFCI PASSES THE ABOVE TEST. DO NOT USE THE SPRAYER IF THE GFCI DOES NOT PASS THE TEST.

PREPARING THE POWER SPRAYER

1. FILL THE 6 GALLON CONTAINER WITH THE CHEMICAL SOLUTION TO BE SPRAYED.
2. SECURE THE FILLED CONTAINER ONTO THE SPRAYER CART WITH THE RESTRAINING BELT.
3. INSERT THE CHEMICAL PICK-UP TUBE FROM THE SPRAYER UNIT INTO THE CONTAINER.
4. CHECK TO BE SURE THAT THE TOGGLE SWITCH ON THE SPRAYER UNIT IS SET TO THE OFF POSITION BEFORE CONNECTING TO AN ELECTRICAL OUTLET.
5. CONNECT THE POWER CORD TO A PROPERLY GROUNDED RECEPTACLE. A 115 VOLT, 60 HZ. SINGLE PHASE 20 AMP CIRCUIT IS REQUIRED.

OPERATING THE POWER SPRAYER

STARTING THE SPRAYER

1. FIRMLY GRIP THE SPRAY GUN IN ONE HAND. BE SURE TO AIM THE GUN IN A SAFE DIRECTION SINCE LIQUID MAY IMMEDIATELY BE DISCHARGED FROM THE END.
2. FLIP THE ON/OFF SWITCH ON THE SPRAYER UNIT TO THE ON POSITION. YOU WILL IMMEDIATELY HEAR THE PUMP WITHIN THE SPRAYER RUN.
3. PULL THE TRIGGER ON THE SPRAY GUN TO DISCHARGE THE SPRAY. THE SPRAY MAY TAKE SEVERAL SECONDS TO APPEAR AFTER THE TRIGGER IS PULLED.
4. DIRECT THE SPRAY ONTO THE AREA TO BE CLEANED UNTIL ALL SURFACES ARE COVERED. ON VERTICAL SURFACES START AT THE TOP APPLYING THE SPRAY WITH A SIDE TO SIDE MOTION WORKING YOUR WAY DOWN.

SHUTTING DOWN AFTER USE

FOLLOWING THESE SIMPLE STEPS CAN PROLONG THE LIFE OF YOUR SPRAYER AND HELP PREVENT SERVICE PROBLEMS.

1. REMOVE THE CHEMICAL PICK-UP TUBE FROM THE 6 GALLON CONTAINER AND PLACE IN A CONTAINER OF CLEAR WARM WATER.
2. RUN THE SPRAYER UNTIL THE SYSTEM IS FLUSHED AND NO CHEMICAL OR SUDS APPEAR FROM THE GUN.
3. REMOVE THE PICK-UP TUBE FROM THE WATER AND RUN THE SPRAYER FOR ONE MINUTE UNTIL MOST OF THE WATER IS EXHAUSTED FROM THE SYSTEM.
4. TURN THE TOGGLE SWITCH TO THE OFF POSITION.
5. WRAP THE SPRAYER HOSE ON THE CART.
6. UNPLUG AND WRAP THE POWER CORD ON THE CART.
7. RINSE THE 6 GALLON CONTAINER WITH FRESH WATER.
8. WIPE THE SPRAYER AND COMPONENTS WITH A DAMP CLOTH.

**NOTE: NEVER STORE THE SPRAYER IN AN AREA WHICH
MAY BE SUBJECT TO FREEZING TEMPERATURES.**